



Thurmalox 270 Aerosol  
SDS Preparation Date (mm/dd/yyyy): 04/27/2022

Page 1 of 9

## SAFETY DATA SHEET

### SECTION 1. IDENTIFICATION

Product identifier used on the label  
: **Thurmalox Black Aerosol Stove Paint**  
Product Code(s) : 270

**Recommended use and restrictions on use:**

Heat resistant paint for wood stoves.  
Recommended restrictions: None Known.

**Name, address, and telephone number of the manufacturer:**

Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.  
02149  
Email: sales@dampney.com  
Supplier's Telephone #: (617) 389-2805

**24 Hr. Emergency Tel # :** Chemtrec 1-800-424-9300

### SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical  
Black aerosol/liquid. Solvent odor.

Classification:

Skin Corrosion/Irritation -	Category 2
Serious eye damage/Eye irritation -	Category 2A
Carcinogenicity –	Category 2
Reproductive Toxicity –	Category 2
Specific target organ toxicity -	Category 3
Specific target organ toxicity (repeated exposure) -	Category 2
Aspiration hazard -	Category 1
Flammable aerosols -	Category 1
Gases under pressure – Compressed Gas	

**Label elements**

Hazard pictogram(s)



*Signal Word*

**DANGER**

Hazard statement(s)

H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.



## SAFETY DATA SHEET

H361 Suspected of damaging fertility or the unborn child.  
H336 May cause drowsiness or dizziness.  
H371 May cause damage to organs (Central Nervous System, Eyes, Kidney, Liver, Respiratory System, and Skin) through prolonged or repeated exposure.  
H305 May be harmful if swallowed and enters airways.

### Prevention:

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, sparks, open flames, hot surfaces. No smoking.  
P280 Wear protective gloves, protective clothing, eye protection, and face protection.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P261 Do not breathe dust, fume, gas, mist, vapours, or spray.  
P271 Use only outdoors or in a well-ventilated area.  
H229 Pressurized container: may burst if heated.  
P211 Do not spray on an open flame or other ignition source.

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/attention.  
P321 Specific treatment see first aid on this label.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/attention.  
P302 + P352 IF ON SKIN: Wash with plenty of water.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER, doctor, or hospital emergency room if you feel unwell.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or hospital emergency room.  
P331 Do NOT induce vomiting.

### Storage:

P403 + P235 (S) Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

### Disposal:

P501 Dispose of contents and empty container in accordance with local, state and federal regulations. Causes skin irritation

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
Acetone	67-64-1	36.00
Propane/Isobutane/n-Butane	68476-86-8	29.100
n-Butyl Acetate	123-86-4	9.96
Toluene	108-88-3	8.26
Xylene	1330-20-7	6.00
Ethyl Benzene	100-41-4	1.30
Carbon Black (Amorphous)	1333-86-4	0.38



## SAFETY DATA SHEET

### SECTION 4. FIRST-AID MEASURES

First aid measures for different exposure routes

**EYES** - flush thoroughly with running water for 15 minutes, including under eyelids. Get medical attention.

**SKIN** - promptly remove contaminated clothing and wash affected areas thoroughly with soap and water. If irritation occurs get medical attention. Wash contaminated clothing thoroughly before re-use.

**INHALATION** - if overcome by vapor, remove to an area free from risk of further exposure. If breathing is difficult, administer oxygen, or artificial respiration if breathing has stopped. Keep person warm and quiet and get medical attention.

**INGESTION** - if swallowed, call a physician immediately. Only induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:**

Pre-existing eye, skin, liver and/or kidney disorders may be aggravated by exposure to this product.

Chronic (long term) exposure: In laboratory animals - overexposure to this material (or its components) has been found to cause the following effects; anemia, liver abnormalities, kidney, lung and spleen damage. In humans - liver and cardiac abnormalities.

Toluene may be harmful to the fetus based on laboratory animal studies. Repeated exposure to toluene has been associated with high frequency hearing loss based on evidence in laboratory animals. The human health consequences of this finding are uncertain.

Chronic overexposure to xylene has been suggested to cause cardiac abnormality in humans.

### SECTION 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:** Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog may be ineffective but should be used to cool fire-exposed containers to prevent pressure build up and possible auto-ignition or explosion when exposed to extreme heat. Water spray. Dry chemical. Carbon Dioxide. Foam. **USE WATER WITH CAUTION.** Material will float and may ignite on surface of water.

**Unsuitable Extinguishing Media:** None known.

**Specific hazards during firefighting:** Do not allow run-off from firefighting to enter drains or water courses.

**Specific extinguishing methods:** Use a water spray to cool fully closed containers.

**Protective Equipment and Precautions for Firefighters:** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Before attempting cleanup, refer to hazard caution information in other sections of this sheet. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

**Large spills** - notify safety personnel. Eliminate potential sources of ignition. Wear appropriate respirator and protective clothing. Soak up with an absorbent, I.E. sand, clay, or other suitable material. Place in non-leaking containers and seal tightly for proper disposal. Ventilate confined spaces. Minimize breathing vapors. Open all windows and doors. Minimize skin contact. Keep product out of sewers and water courses by diking and impounding. Observe precautions for volatile, combustible vapors from absorbed material.

**Small spills** - take up with absorbent material and place in non-leaking containers for proper disposal.

Precautions for safe handling

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling:

Avoid contact with eyes. Avoid breathing vapors or mists. Avoid skin contact. Use with adequate ventilation. Keep away from heat, flames, and all other sources of ignition. Keep away from all sources of electricity such as electric motors and batteries.



Thurmalox 270 Aerosol  
SDS Preparation Date (mm/dd/yyyy): 04/27/2022

Page 4 of 9

## SAFETY DATA SHEET

Conditions for safe storage, including any incompatibilities  
Technical measures/Storage conditions: Keep containers tightly closed in a cool, well-ventilated place.

### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Occupational Exposure Limits

	ACGIH TLV TWA	OSHA PEL TWA
Acetone	250.00 Ppm	1000.00 Ppm
Propane/Isobutane/N-Butane	1000.00 Ppm	1800.00 Mg/M3
N-Butyl Acetate	150.00 Ppm	150.00 Ppm
Toluene	20.00 Ppm	200.00 Ppm
Xylene (Haps)	100.00 Ppm	100.00 Ppm
Ethyl Benzene	20.00 Ppm	100.00 Ppm
Carbon Black (Amorphous)	N/A	3.5 mg/m <sup>3</sup>

#### Respiratory Protection:

Use NIOSH approved respirator as required to prevent overexposure.

Unconfined spaces - use a vapor/particulate respirator such as NIOSH approved No. TC-23C.

Confined spaces - use a constant flow air-line respirator such as NIOSH approved NO. TC-19C.

#### Ventilation:

Provide sufficient ventilation to keep air contaminant concentration below current applicable OSHA permissible exposure limit or ACGIH's TLV limit. No smoking or open lights.

#### Protective Gloves:

Use chemical-resistant gloves to prevent skin contact.

#### Eye Protection:

Use chemical splash goggles or face shield to prevent eye contact.

#### Other Protective Equipment:

Use chemical-resistant or other protective outerwear to protect against clothing contamination and skin contact.

#### Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid and gas under pressure
Appearance/Color:	Black
pH Value:	Not Applicable
Boiling Range:	-43.7°F - 293.0°F
Melting Point:	Not Applicable
Evaporation Rate:	5.379 times faster than n-Butyl Acetate
Vapor Density:	Heavier than air
Partition Coefficient	Not Available
% Volatile Weight	92.12%
% Volatile Volume	96.70%
Specific Gravity:	0.78893
Weight/Gallon:	6.6 lbs
VOC	5.77 LBS/GAL



Thurmalox 270 Aerosol  
SDS Preparation Date (mm/dd/yyyy): 04/27/2022

Page 5 of 9

## SAFETY DATA SHEET

Heavy Elements (ppm) 0.0  
Flammability Class 1A  
Flash Range: -156.0°F – 84.2°F  
Explosive Range: 1.0% - 19.0%

### SECTION 10. STABILITY AND REACTIVITY

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur  
Incompatibility: Avoid contact with strong oxidizing agents, acids or bases.  
Conditions to Avoid: Avoid heat, open flames.  
Hazardous Decomposition Products: Carbon monoxide and unidentified organics may be formed.

### SECTION 11. TOXICOLOGICAL INFORMATION

	Route	Species	Exposure and Dose
Acetone	Inhalation	Rat	LC50 8 HOURS 50,100 mg/m <sup>3</sup>
	Oral	Rat	LD50 5,800. mg/kg
N-Butyl Acetate	Inhalation	Rat	LC50 390. PPM
	Oral	Rat	LD50 10,768. mg/kg
	Skin	Rabbit	LD50 17,600. mg/kg
Toluene (Haps)	Inhalation	Rat	LC50 4 HOURS 12.5. mg/L
	Oral	Rat	LD50 2,600. mg/kg
	Skin	Rabbit	LD50 12,000. mg/kg
Xylene (Haps)	Inhalation	Rat	LC50 4 HOURS 29.08 mg/l
	Oral	Rat	LD50 3,500 mg/kg
	Skin	Rabbit	LD50 4,350. mg/kg
Ethyl Benzene (Haps)	Inhalation	Rat	LC50 4 HOURS 17.2 mg/l
	Oral	Rat	LD50 3500 mg/kg
	Skin	Rabbit	LD50 15400. mg/kg
Carbon Black (Amorphous)	Inhalation	Rat	NOEL 1 mg/l <sup>3</sup>
	Oral	Rat	LD50 8000 mg/kg
	Skin	Rabbit	N/Av

#### Reproductive toxicity

Toluene: Case studies of person abusing toluene suggest isolated incidences of adverse effects on the fetus including birth defects.

#### Carcinogenic toxicity

Toluene: No data available

Product	OSHA	IARC	NTP
Toluene	-	3	-
Xylene	-	3	-



Thurmalox 270 Aerosol  
 SDS Preparation Date (mm/dd/yyyy): 04/27/2022

**SAFETY DATA SHEET**

Ethyl Benzene - 2B -

**EFFECTS OF OVEREXPOSURE:**

Primary route(s) of entry:

(X) Dermal (X) Inhalation ( ) Ingestion

**SECTION 12. ECOLOGICAL INFORMATION**

**TOXICITY**

PRODUCT	RESULT	SPECIES	EXPOSURE
Toluene	EC50 433 ppm	Algae – Skeletonema Costatum	96 hours
	EC50 12,500 Micrograms/liter Fresh Water	Algae - Pseudokirchneriella Subcapitata	72 hours
	EC50 11,600 Micrograms/liter Fresh Water	Crustaceans – Gammarus pseudolimnaeus – Adult	48 hours
	EC50 6,000 Micrograms/liter Fresh Water	Daphnia – Daphnia magna Juvenile	48 hours
	LC50 5,500 Micrograms/liter Fresh Water	Fish – Oncorhynchus kisutch – Fry	96 hours
	NOEC 500,000 Micrograms Fresh Water	Algae – Pseudokirchneriella subcapitata	96 hours
	NOEC 1,000 Micrograms/liter Fresh Water	Daphnia – Daphnia magna	21 days
Xylene	LC50 13.4 Micrograms/liter	Pimephales promelas	96 hours flow-through
	LC50 2.661-4.09 Micrograms/liter	Fish – Oncorhynchus mykiss	96 hours static
	LC50 13.5-17.3 Micrograms/liter	Fish – Oncorhynchus mykiss	96 hours
Ethyl Benzene	EC50 4.6 Micrograms/liter	Algae - Pseudokirchneriella Subcapitata	72 hours
	EC50 438 Micrograms/liter	Algae - Pseudokirchneriella Subcapitata	96 hours
	EC50 2.6-11.3 Micrograms/liter	Algae - Pseudokirchneriella	72 hours static



### SAFETY DATA SHEET

		Subcapitata	
	LC50 11.0-18.0 Micrograms/liter	Fish – Oncorhynchus mykiss	96 hours static
	LC50 4.2 Micrograms/liter	Fish – Oncorhynchus mykiss	96 hours static
	EC50 1.8-2.4 Micrograms/liter	Daphnia – Daphnia magna	48 hours
Carbon Black	N/Av	Algae	
	LC50 >1000 mg/l	Fish – Zebrafish	96 hours static
	EC50 >5600 mg/l	Daphnia – Water Flea	48 hours

### SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal : Handle in accordance with good industrial hygiene and safety practice.  
 Methods of Disposal : Dispose in accordance with all applicable regulations.

### SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT		Limited Quantity			
IMDG		Limited Quantity			
ICAO/IATA	UN1950	Aerosols, Flammable	2.1		

### SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

Ingredient	TSCA	DSL	CERCLA RQ
Acetone	Y	Y	5,000 lbs
Butyl Acetate	Y	Y	5,000 lbs
Toluene	Y	Y	1,000 lbs
Xylene	Y	Y	100 lbs
Ethyl Benzene	Y	Y	1,000 lbs

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
Toluene	108-88-3	8.26%
Xylene	1330-20-7	6.00%



Thurmalox 270 Aerosol  
SDS Preparation Date (mm/dd/yyyy): 04/27/2022

Page 8 of 9

## SAFETY DATA SHEET

Ethyl Benzene 100-41-4 1.30%

### WHMIS

Class A: Compressed gas  
Class B5: Flammable aerosol  
Class D2B: Toxic materials

### RIGHT TO KNOW

Ingredient	CAS	New Jersey	Massachusetts	Pennsylvania
Acetone	67-64-1	Y	Y	Y
Toluene	108-88-3	Y	Y	Y
Butyl Acetate	123-86-4	Y	Y	Y
Xylene	1330-20-7	Y	Y	Y
Ethyl Benzene	100-41-4	Y	Y	Y

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Prop 65
Toluene	108-88-3	Developmental
Ethyl Benzene	100-41-4	Carcinogen

## SECTION 16. OTHER INFORMATION

### NFPA

Health hazard 2  
Flammability 3  
Reactivity 0

### Legend:

ACGIH: American Conference of Governmental Industrial Hygienists  
AICS: Australian Inventory of Chemical Substances  
CA: California  
CAS: Chemical Abstract Services  
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980  
CFR: Code of Federal Regulations  
CSA: Canadian Standards Association  
DOT: Department of Transportation  
EC50: Effective Concentration 50%.  
EINECS: European Inventory of Existing Commercial chemical Substances  
ENCS: Existing and New Chemical Substances  
EPA: Environmental Protection Agency  
HMIS: Hazardous Materials Identification System  
HSDB: Hazardous Substances Data Bank  
IARC: International Agency for Research on Cancer  
IECSC: Inventory of Existing Chemical Substances  
IMDG: International Maritime Dangerous Goods  
Inh: Inhalation  
KECI: Korean Existing Chemicals Inventory  
KECL: Korean Existing Chemicals List  
LC: Lethal Concentration  
LD: Lethal Dose  
N/Ap: Not Applicable  
N/Av: Not Available  
NFPA: National Fire Protection Association





Dampney Company, Inc.  
85 Paris Street  
Everett, Massachusetts, U.S.A.02149  
Email: sales@dampney.com  
Telephone: (617) 389 2805

**Thurmalox 270 Aerosol**  
**SDS Preparation Date (mm/dd/yyyy): 04/27/2022**

**Page 9 of 9**

## **SAFETY DATA SHEET**

NJ: New Jersey  
NIOSH: National Institute of Occupational Safety and Health  
NOEC: No observable effect concentration  
NTP: National Toxicology Program  
OECD: Organization for Economic Co-operation and Development  
OSHA: Occupational Safety and Health Administration  
PA: Pennsylvania  
PEL: Permissible exposure limit  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
RCRA: Resource Conservation and Recovery Act  
RTECS: Registry of Toxic Effects of Chemical Substances  
SARA: Superfund Amendments and Reauthorization Act  
STEL: Short Term Exposure Limit  
TDG: Canadian Transportation of Dangerous Goods Act & Regulations  
TLV: Threshold Limit Values  
TPQ: Threshold Planning Quantity  
TSCA: Toxic Substance Control Act  
TWA: Time Weighted Average  
WHMIS: Workplace Hazardous Materials Identification System

### **References:**

ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2015.  
Canadian Centre for Occupational Health and Safety, CCIInfoWeb Databases, 2016 (Chempendium, RTECs, HSDB, INCHEM).  
IARC Monographs. Overall Evaluation of Carcinogenicity  
Material Safety Data Sheet from manufacturer.  
OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2015.  
California Proposition 65 List

Prepared by Dampney Company, Inc.  
85 Paris Street  
Everett, MA 02149

Tel. 617-389-2805  
Fax. 617-389-0484  
Email mail@dampney.com

**Preparation Date (mm/dd/yyyy): 04/27/2022**

### **Other special considerations for handling**

: Provide adequate information, instruction and training for operators.

### **DISCLAIMER**

The information and recommendations contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or the user to ensure that this material is properly and safely used.

**Last Page**