



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 1 of 9

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label: Thurmalox Black
Product Code(s): 270

Recommended use and restrictions on use: Heat resistant coating
Recommended restrictions: None Known.

Name, address, and telephone number of the manufacturer:
Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149

Email: sales@dampney.com
Supplier's Telephone: (617) 389-2805

24 Hr. Emergency Tel: Chemtrec 1-800-424-9300 (Within North America)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical
Black liquid. Solvent odor.

Classification:
Flammable Liquids - Category 2
Skin Irritation - Category 2
Serious eye damage/eye irritation - Category 2A
Carcinogen - Category 2
Reproductive Toxicity - Category 2
Specific Target Organ Toxicity, Single Exposure - Category 3 narcotic effects
Specific Target Organ Toxicity, Single Exposure -Category 3 (respiratory)
Specific Target Organ Toxicity, Repeated Exposure - Category 2 (CNS)

Label elements

Hazard pictogram(s)



Signal Word
DANGER

Hazard statement(s)
Highly flammable liquid and vapour.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
Suspected of damaging the unborn child.
May cause drowsiness or dizziness.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statement(s)
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 2 of 9

SAFETY DATA SHEET

Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe mist or vapor.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/clothing and eye/face protection.

Response

If exposed or concerned: Get medical attention/advice.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.
If skin irritation occurs, get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.

In case of fire: Use water fog, dry chemical, CO2, or 'alcohol' foam for extinction.

Storage

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

Disposal

Dispose of contents/container in accordance with local regulation.

Other hazards

No OSHA defined hazard classes.
Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. This product contains Manganese compounds. Chronic manganese exposures can lead to neurological problems such as apathy, drowsiness, weakness, spastic gait, paralysis, and other neurological problems resembling Parkinsonism. These symptoms can become progressive and permanent if not treated.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
Xylene	1330-20-7	30.67
Toluene	108-88-3	26.89
Ethyl Benzene	100-41-4	6.26
Carbon Black	1333-86-4	2.53
n-Butanol	71-36-3	2.53
Manganese Compounds	75864-23-2	2.05
Ethanol	64-17-5	1.75

SECTION 4. FIRST-AID MEASURES

First aid measures for different exposure routes

EYES – For eye contact, flush with running water for at least 15 minutes. If eye irritation persists: get medical advice / attention.
SKIN – Immediately flush with plenty of water, while removing contaminated clothing. Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.
INHALATION – If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration.



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270

SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 3 of 9

SAFETY DATA SHEET

If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.

INGESTION – Immediately call a POISON CENTER or doctor/physician. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.

Most important symptoms and effects, both acute and delayed: Causes skin irritation. Redness, swelling, itching and dryness. May cause respiratory irritation. May cause coughing and breathing difficulties. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause headache, nausea, dizziness, and other symptoms of central nervous system depression. Causes serious eye irritation. Symptoms may include stinging and tearing. Prolonged exposure can cause central nervous system effects. Contains a chemical or chemicals which can cause birth defects or other reproductive harm. Suspected of causing cancer. Chronic overexposure to xylene has been suggested to cause cardiac abnormality in humans.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Carbon dioxide (CO₂); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting: Highly flammable liquid and vapour. Vapours may ignite explosively. Vapours are heavier than air and may spread along floors. Static discharge, impact, friction, and heat may ignite exposed chemical material.

Empty containers may contain hazardous residues.

Hazardous combustion products: Carbon dioxide, carbon monoxide, and other unidentified organic compounds.

Special fire-fighting procedures: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Do not breathe fumes or vapours. Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from firefighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Steps to be taken in case material is released or spilled: Before attempting cleanup, refer to hazard caution information in other sections of this sheet. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Large spills - notify safety personnel. Eliminate potential sources of ignition. Wear appropriate respirator and protective clothing. Soak up with an absorbent, I.E. sand, clay, or other suitable material. Place in non-leaking containers and seal tightly for proper disposal. Ventilate confined spaces. Minimize breathing vapors. Open all windows and doors. Minimize skin contact. Keep product out of sewers and water courses by diking and impounding. Observe precautions for volatile, combustible vapors from absorbed material.

Small spills - take up with absorbent material and place in non-leaking containers for proper disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with eyes. Avoid breathing vapors or mists. Avoid skin contact. Use with adequate ventilation. Keep away from heat, flames, and all other sources of ignition. Keep away from all sources of electricity such as electric motors and batteries.

Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

Chemical Name	ACGIH TLV TWA	OSHA PEL TWA
Xylene	100.00 ppm	100.00 ppm (435 mg/m ³)



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A.02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270

SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 4 of 9

SAFETY DATA SHEET

Toluene	20.00 ppm	200.00 ppm
Ethyl Benzene	20.00 ppm	100.00 ppm (435 mg/m ³)
Carbon Black	N/A	N/A
n-Butyl Alcohol	20.00 ppm	100.00 ppm (300 mg/m ³)
Manganese Compounds	N/A	N/A
Ethanol	1000.00 ppm	1000.00 ppm (1900 mg/m ³)

Respiratory Protection: Use NIOSH approved respirator as required to prevent overexposure.

If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Ventilation and engineering measures:

Provide sufficient ventilation to keep air contaminant concentration below current applicable OSHA permissible exposure limit or ACGIH's TLV limit. No smoking or open lights.

Protective Gloves: Use chemical-resistant gloves to prevent skin contact.

Eye Protection: Use chemical splash goggles or face shield to prevent eye contact.

Other Protective Equipment: Use chemical-resistant or other protective outerwear to protect against clothing contamination and skin contact.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Appearance/Color: Black
Odor: Solvent
pH Value: Not Applicable
Boiling Range: 173.3°F - 284.0°F
Melting Point: Not Applicable
Evaporation Rate: 0.243 times faster than n-Butyl Acetate

Vapor Density: Heavier than air

Partition Coefficient: Not Available
% Volatile Weight: 68.0%
% Volatile Volume: 81.0%
Specific Gravity: 1.03454
Weight/Gallon: 8.62 lbs
VOC: 5.9 LBS/GAL
Heavy Elements (ppm): 0.0

Flammability Class: 1B
Flash Range: 45.0°F
Explosive Range: 1.0% - 7.4%

SECTION 10. STABILITY AND REACTIVITY

Stability: This product is stable

Hazardous Polymerization: Hazardous polymerization will not occur

Incompatibility: Avoid contact with strong oxidizing agents, acids, or bases.

Conditions to Avoid: Avoid heat, open flames.

Hazardous Decomposition Products: Carbon monoxide and unidentified organics may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

Routes of Exposure:

Inhalation: Yes



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270

SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 5 of 9

SAFETY DATA SHEET

Skin & Eye: Yes
Ingestion: Yes
Skin Absorption: Yes

Signs and symptoms of short-term (acute) exposure

Signs and symptoms of inhalation: May cause respiratory tract irritation. Coughing, difficulty breathing, and tightness in chest. May cause headache, nausea, dizziness, and other symptoms of central nervous system depression.

Signs and symptoms of ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Signs and symptoms of skin: Causes skin irritation. Symptoms may include redness, edema, drying defatting and cracking of the skin.

Sign and symptoms of eyes: Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects: Prolonged exposure can cause central nervous system effects. Chronic manganese exposures can lead to neurological problems such as apathy, drowsiness, weakness, spastic gait, paralysis, and other neurological problems resembling Parkinsonism. These symptoms can become progressive and permanent if not treated

Mutagenicity: Not expected to be mutagenic in humans.

Carcinogenicity: This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification: Carcinogenicity- Category 2 Suspected of causing cancer.

Contains Ethylbenzene. Ethylbenzene is classified as carcinogenic by IARC (Group 2B) and ACGIH (Category A3).

Reproductive effects and Teratogenicity

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Classification: Reproductive Toxicity - Category 2 Suspected of damaging the unborn child.

Contains Toluene. Toluene may cause fetotoxic effects at doses which are not maternally toxic, based on animal data.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects:

This material is classified as hazardous under OSHA regulations (29CFR 1910.1200)

(Hazcom 2012). Classification: Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or dizziness. May cause respiratory irritation

Specific target organ toxicity (STOT), repeated exposure - Category 2 May cause damage to the central nervous system through prolonged or repeated exposure if inhaled.

Medical conditions aggravated by overexposure: Pre-existing skin, eye, respiratory and central nervous system disorders.

Chemical Name	Route	Species	Exposure	Dose
Xylene (Haps)	Inhalation	Rat	LC50 4 Hours	6350. ppm (27.6 mg/l)
	Oral	Rat	LD50	3253. mg/kg
	Skin	Rabbit	LD50	12180. mg/kg
Toluene (Haps)	Inhalation	Rat	LC50 4 Hours	7585. ppm (28.1 mg/l)
	Oral	Rat	LD50	5580. mg/kg
	Skin	Rabbit	LD50	12125. mg/kg
Ethyl Benzene (Haps)	Inhalation	Rat	LC50 4 Hours	4000. ppm (17.4 mg/l)
	Oral	Rat	LD50	3500. mg/kg
	Skin	Rabbit	LD50	15380. mg/kg
Carbon Black	N/A	N/A	N/A	N/A



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A.02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 6 of 9

SAFETY DATA SHEET

N-Butyl Alcohol	Inhalation	Rat	LC50 4 Hours	8000. ppm (24.3 mg/l)
	Oral	Rat	LD50	790. - 4360. mg/kg
	Skin	Rabbit	LD50	3402. mg/kg
Manganese Compounds	N/A	N/A	N/A	N/A
Ethanol	Inhalation	Rat	LC50 4 Hours	30000. mg/kg
	Oral	Rat	LD50	10470. mg/kg
	Skin	Rabbit	LD50	15800. mg/kg

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product	Result	Species	Exposure
Xylene	LC50 8.2 mg/l	Rainbow trout	96 hours
	EC50 3.2 – 9.56mg/l	Daphnia magna	48 hours
	EC50 3.2 – 4.9 mg/l	Green Algae	96 hours
Toluene	LC50 5.4 mg/l	Pink Salmon	96 hours
	EC50 3.78 mg/l	Water flea	48 hours
	N/A	N/A	N/A
Ethyl Benzene	LC50 4.2 mg/l	Rainbow trout	96 hours
	EC50 1.81 mg/l	Daphnia magna	48 hours
	EC50 3.6 mg/l	Green Algae	96 hours
Carbon Black	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
Manganese Compounds	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
n-Butyl Alcohol	LC50 1376 mg/l	Fathead minnow	96 hours
	EC50 1328 mg/l	Daphnia magna	48 hours
	N/A	N/A	N/A
Ethanol	LC50 14200 mg/l	Fathead minnow	96 hours
	LC50 5012 mg/l	Daphnia magna	48 hours
	EC50 275 mg/l	Green Algae	72 hours

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal: Handle in accordance with good industrial hygiene and safety practice.



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A.02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 7 of 9

SAFETY DATA SHEET

Methods of Disposal: Dispose in accordance with all applicable regulations.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1263	Paint	3	II	
Additional Information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 liters; in packages not exceeding 30 kg gross mass.				
IMDG	UN1263	Paint	3	II	
Additional Information	May be shipped as Limited Quantity when transported in containers no larger than 5.0 liters; in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1263	Paint	3	II	
Additional Information	Refer to the appropriate Packing Instruction, prior to shipping this material.				

SECTION 15 - REGULATORY INFORMATION

U.S. Federal Regulations

Ingredient	TSCA	DSL	CERCLA RQ
Xylene	Y	Y	100 lbs
Toluene	Y	Y	1,000 lbs
Ethyl Benzene	Y	Y	1,000 lbs
Carbon Black	Y	Y	N/A
n-Butyl alcohol	Y	Y	5,000 lbs
Manganese Compound	Y	Y	N/A
Ethanol	Y	Y	N/A

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Chemical Name	CAS Number	Percent
Xylene	1330-20-7	30.67%
Toluene	108-88-3	26.89%
Ethyl Benzene	100-41-4	6.26%
Carbon Black	1333-86-4	2.53
n-Butyl Alcohol	71-36-3	2.53%
Manganese Compounds	75864-23-2	2.05%
Ethanol	64-17-5	1.75

WHMIS
Class B2: Flammable liquid



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A.02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 8 of 9

SAFETY DATA SHEET

Class D2A: Very toxic material

RIGHT TO KNOW

Ingredient	CAS	New Jersey	Massachusetts	Pennsylvania
Xylene	1330-20-7	Y	Y	Y
Toluene	108-88-3	Y	Y	Y
Ethyl Benzene	100-41-4	Y	Y	Y
Carbon Black	1333-86-4	n/a	n/a	n/a
n-Butyl Alcohol	71-36-3	Y	Y	Y
Manganese Compounds	75864-23-2	n/a	n/a	n/a
Ethanol	64-17-5	Y	Y	Y

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Prop 65
Toluene	108-88-3	Developmental
Ethyl Benzene	100-41-4	Carcinogen

SECTION 16. OTHER INFORMATION

NFPA

Health hazard	2
Flammability	3
Reactivity	0

Legend:

ACGIH: American Conference of Governmental Industrial Hygienists
AICS: Australian Inventory of Chemical Substances
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CSA: Canadian Standards Association
DOT: Department of Transportation
EC50: Effective Concentration 50%.
EINECS: European Inventory of Existing Commercial chemical Substances
ENCS: Existing and New Chemical Substances
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IECSC: Inventory of Existing Chemical Substances
IMDG: International Maritime Dangerous Goods
Inh: Inhalation
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NJ: New Jersey
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration



Dampney Company, Inc.
85 Paris Street
Everett, Massachusetts, U.S.A. 02149
Email: sales@dampney.com
Telephone: (617) 389 2805

Thurmalox 270
SDS Preparation Date (mm/dd/yyyy): 01/22/2025

Page 9 of 9

SAFETY DATA SHEET

NTP: National Toxicology Program
OECD: Organization for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TPQ: Threshold Planning Quantity
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References:

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015
European Chemicals Agency, Classification Legislation, 2015 Material Safety Data Sheet from manufacturer.

Preparation Date (mm/dd/yyyy): 01/22/2025

Other special considerations for handling: Provide adequate information, instruction, and training for operators.

Dampney Company, Inc.
85 Paris Street
Everett MA 02149 U.S.A
Telephone: (617) 389-2805
Please direct all inquiries to Dampney Company.



DISCLAIMER

This Safety Data Sheet was prepared by Dampney Company, Inc. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. Dampney Company, Inc expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Dampney Company, Inc.

Last Page